



潍坊昌盛复合材料有限公司

WEIFANG CHANGSHENG COMPOSITE MATERIAL CO., LTD

No.180, Venture Road, Beiguan Venture Park, Baodu Street, Changle, Weifang, Shandong, China

TEL/FAX:86-536-6236781 86-18053682187 EMAIL: changshengmaterial@163.com WEB: www.changshengmaterial.com

PVC Liquid Ca-Zn Stabilizer CZ-102

Technical Data Sheet

Introduction:

Ca/Zn stabilizer CZ-102 is liquid composite heat stabilizer.

Item NO.:CZ-102

HS Code: 381239

Technical specifications:

| Item | Specifications |
|---|-------------------------------------|
| Appearance | White or little yellow clear liquid |
| Colour (Pt-Co value) | ≤ 50 |
| Viscosity (25°C, mPa·S) | 40-80 |
| Specific Gravity (25°C, g/cm ³) | 0.85±0.05 |
| Metal oxides (%) | 2.0±0.2 |
| Suggested usage PHR | 1-2 |

Features:

- Long-term heat stability.
- Excellent processability, flowability and compatibility.
- Excellent transparency.
- Environmentally friendly, can be used for packaging material.

Applications:

- Suitable for processing various soft and transparent PVC products (hose, film, shoes, wires and cables, toys, etc.). Recommended to use it with esbo oil.

Package:

Packed into plastic drum, 180kg/drum

Storage and transport:

The product is nonflammable, non-toxic and non-explosive.

Please keep in a cool and dry place with cover facing up to prevent water.





潍坊昌盛复合材料有限公司

WEIFANG CHANGSHENG COMPOSITE MATERIAL CO., LTD

No.180, Venture Road, Beiguan Venture Park, Baodu Street, Changle, Weifang, Shandong, China

TEL/FAX:86-536-6236781 86-18053682187 EMAIL: changshengmaterial@163.com WEB: www.changshengmaterial.com

PVC Liquid Ca-Zn Stabilizer CZ-187

Technical Data Sheet

Introduction:

Ca/Zn stabilizer is liquid composite heat stabilizer. Add some methyl tin mercaptide heat stabilizer to get more better stability.

Item NO.: CZ-187

HS Code: 381239

Technical specifications:

| Item | Specifications |
|---|------------------------------|
| Appearance | White transparent oil liquid |
| Colour (Pt-Co value) | ≤ 50 |
| Viscosity (25°C, mPa·S) | 70-100 |
| Specific Gravity (25°C, g/cm ³) | 0.90±0.05 |
| Metal oxides (%) | 4.5±0.2 |
| Suggested usage PHR | 1-2 |

Features:

- Long-term heat stability.
- Excellent processability, flowability and compatibility.
- Excellent transparency.
- Environmentally friendly, can be used for packaging material.
-

Applications:

- Suitable for processing various soft and transparent PVC products (hose, film, shoes, wires and cables, toys, etc.). Recommended to use it with esbo oil.

Package:

Packed into plastic drum, 180kg/drum

Storage and transport:

The product is nonflammable, non-toxic and non-explosive.

Please keep in a cool and dry place with cover facing up to prevent water.

